

The RC-15T is a trailer-mounted drilling machine that can be towed by most pick up trucks in the market. It is a fully hydraulic machine designed for drilling with reverse circulation equipment and tools for sample recovery.

Conventional drilling can be done.

The RC-15T is designed to drill up to 30 meters with a 4" (100mm) Reverse circulation down the hole hammer.

Using conventional drilling methods and tools the rig may achieve a depth of up to 75m.

(Depths depend on the ground formation, operator skill, compressor capacity and weight of the tools being used)

APPLICATIONS

- Seismic
- Mineral Exploration
- Micropiling
- Access Roads
- Anchoring
- Blasting
- Water Well
- Servicing holes etc.



RC-15T

DIMENSIONS & WEIGHT

Length 3550mm
Width 2.1mm
Height 3600mm
Weight 1.6 tons

ENGINE

Type Diesel / Gasoline Rated power 36 hp Cooling System air

HYDRAULIC SYSTEM

Pump Double gear pump
Tank Capacity 45L
Cooling System air
Operating Pressure 170bar

FEED

Head Travel 1800mm Pull up capacity 2000kgs









ROTATIONAL SYSTEM

Type Hydraulic motor
Rotational Speed 95 rpm
Torque 122kg-m (1220 Nm)
Swivel for compilation of sample

DUST COLLECTOR

Type Cyclon
Capacity 700 cfm

STABILIZER

4 hydraulic jacks allows the machine to be leveled in most terrains more efficiently.

DRILLING CAPACITY

Max. Diameter $4 \frac{1}{2}$ "(108mm) Max. Depth 30m



Email: secura@cyber.net.pk Website: www.secura-group.com